

RENTAL PACKAGE

150 KW ELECTRIC HEATER ATTACHMENT (ACCESSORY TO 30 TON DX UNIT)

DESCRIPTION

This heater is designed for use with the Ohio Cat 30 ton DX unit. The unit has a flanged opening that buts up to the supply air output of the 30 ton DX unit. It uses the 10,000 CFM VFD blower of the 30 ton DX unit as the air flow source.

SPECIFICATIONS

Model	150kW Electric Heater Attachment
Dimensions	
Height	56"
Width	48"
Depth	26"
	500 lbs

APPLICATIONS

- Job Site/Construction Heat
- General/Building Heat
- · Temporary Shelter
- Industrial Heat
- · Commercial/Institutional Heating

TECHNICAL DATA

Electrical Data	460 volt/3 phase/60 Hertz 225 amp 600 volt single pole mount receptacles 180 FLA
Heat Control	Programmable Logic Control 160° Temp Internal Thermostat 103° Temp Remote Thermostat On/Off Switch
Machine Control	On/Off/Heat Switch 75 or 150 kw operation Indicator lights (power/air flow/heat/over temp)
General	Powder coated steel construction Fork lift pockets

Consult your Ohio CAT representative for more details.

©2014 Ohio CAT All rights reserved. Materials and specifications are subject to change without notice.

