

# FROST Fighter

## IDH500QR

Available in Oil/Diesel (LP/NG Coming Soon!)

*Not only is it the most efficient, durable and reliable Indirect Fired Heater available in its class, the IDH500QR is also the one of the quietest at <62dB and offers some the most versatile performance features available including standard recirculation for MAXIMUM fuel efficiency savings!*



### Features:

- Proven & reliable commercial grade burner
- Over 81% efficiency
- Fully Insulated Jacket to minimize heat loss, increase efficiency and provide cool to the touch for safety
- Proven "Multi-Pass" Stainless Steel Heat Exchanger provides unsurpassed heat transfer
- Fully independent fan & combustion air provides consistent and dependable operation in cold weather and ensures pre-heating to eliminate cold air delivery at start-up
- High static pressure/high volume fan provides large volumes of air movement with or without ducting attached
- Available with Dual 12" or Single 16" Outlet that can accommodate up to 100ft. of supply duct
- 16" Intake that can accommodate up to 50ft. of return duct to significantly reduce fuel consumption and heating times (*length of intake duct attached requires equal reduction from 100ft. of supply duct ..e.g: 25ft intake = 75ft supply*)
- Compact design with highly durable 6-Ply Pneumatic tires, handles & lifting bail for easy transport
- Quiet operation of <62dB for noise sensitive areas
- Durable powder coat finish
- High efficiency stainless steel heat exchanger
- Optional remote thermostat and 60 US Gallon Double-wall Environmental Fuel Tank are available
- **CSA Approved**

### Specifications:

Maximum Heating Capacity:	500,000 BTU/h
Fuel Requirement:	Oil/Diesel
Heated Air Volume:	4,800 CFM
Operational Temp. Rating:	-40°C or Colder
Maximum Static Pressure:	3.5"
Discharge Temperature:	Up To 250°F (121°C)
Decibel Rating:	<65dB

Standard Fuel Tank Capacity:	42/opt. 60 US Gallons
Approx. Run Time (Std/Opt):	14/20 hrs
Standard Recirculation:	Yes
Overall Dimensions (LxWxH):	70" x 35" x 57"
Approximate Dry Weight:	420lbs
Approximate Weight w/ Fuel:	580lbs
Required Power:	120V/20amp/60Hz

**WE. KNOW. HEAT.**