



RENTAL UNIT 600,000 BTU Make-up Air Heater

SPECIFICATIONS

Model.....MUA600
 Dimensions
 Length.....60.5"
 Width.....29.25"
 Height.....48"
 Shipping Weight.....500
 lbs Duct Connection-.....20" Outlet
 fl ange Power supply.....115 volt/1
 phase/60 Hertz

APPLICATIONS

- Job Site/Construction Heat
- General Building Heat
- Temporary Shelter
- Industrial Heat
- Commercial/Institutional Heating



TECHINCAL DATA

Electrical/Motor Horsepower Full Load Amps Maximum Unit Ampacity	1.5 HP 12 FLA 20 amps
Fuel Type Consumption rate Burner type Inlet pressure Maximum manifold pressure Minimum gas supply	Natural Gas/Propane 100,000 BTU/hr (min) / 600,000 BTU/hr (max) Modulating Inlet pressure (min/max): 5 in. wc (min) / 2 psi (max) 5 in. wc 7 in wc for maximum input adjustment
Blower Speed Drive mechanism Duct outlet	3500 CFM Belt Drive 20" diameter outlet flange
Heat Thermostat Maximum temperature rise Maximum discharge temperature	Remote/Stationary 240 °F 220 °F
General Body Mobility Portability	Stainless steel construction 8" lockable castors Fork lift pockets/Lifting eye

Consult your Caterpillar representative for more details.

www.CAT-ElectricPower.com
 ©2007 Caterpillar
 All rights reserved.
 Printed in U.S.A.

Materials and specifications are subject to change without notice.