



931 Jeanette Avenue
 Middletown, OH 45042
 1-800-221-9234
 T: (513) 422-3639
 F: (513) 422-9688

QK-WI

INDUSTRIAL HVAC DUCTING

Manufactured with high-strength sewn construction, reinforced with high tensile wire and enhanced with an abrasion resistant wearstrip around the circumference of the duct. Standard end finish includes our wire round end ring.

Applications include industrial and special event air conditioning, moderate heating, air-blowing and drying.



SPECIFICATIONS	
DIAMETER RANGE	8 - 36" (203 - 915mm)
STANDARD	25' (7.6m)
STANDARD COLOR	Yellow / White
PITCH	7" (18cm) - SUPPLY AIR
TEMPERATURE	-40 to 200°F (-40 to 93°C)
INSULATION COMPOSITION	3-PLY THERMAL BARRIER

- Quik-Kleen (QK-WI) insulated product line is constructed using a three-ply PVC insulated fabric composition with a special **Urethane** topcoat exterior.
- The Urethane topcoat forms a barrier that aids in preventing dirt from sticking to the fabric, allowing the duct to be easily cleaned.
- Insulation includes a layer of foil to help refract radiation from sunlight.
- Insulated composition helps to reduce overall heat gain and protects conditioned air over long lengths.
- This product line includes hanging tabs along the length.

END FINISH

WIRE ROUND END RING
Wire ring encased in fabric interlocks one duct to another. This is our standard end finish.



SOFT CUFF WITH STRAP (CLIP)
Smaller diameters use a 1" (25mm) steel clip buckle.



SOFT CUFF
Folded fabric forms a 4" (102mm) finished cuff.



SOFT CUFF WITH STRAP (CAM)
Larger diameters use a 1" (25mm) cam buckle.





931 Jeanette Avenue
 Middletown, OH 45042
 1-800-221-9234
 T: (513) 422-3639
 F: (513) 422-9688

GSL-W

INDUSTRIAL HVAC DUCTING

Manufactured with our high-strength PVC reinforced polyester fabric. Products are available with bi-directional airflow construction, are reinforced with high tensile wire and enhanced with an abrasion resistant wearstrip around the circumference of the duct. Standard end finish includes our wire round end ring.

Applications include confined space ventilation, air conditioning, general air circulation, air-blowing and drying.



SPECIFICATIONS	
DIAMETER RANGE	4 – 36" ID (102 – 915mm)
STANDARD LENGTH	25' (7.6m)
STANDARD COLOR	Yellow / White / Blue
PITCH	2 – 6" (5 – 15.2cm)
TEMPERATURE RATING	-40 to 200°F (-40 to 93°C)
FABRIC WEIGHT	13oz/yd ² (441g/m ²)

- Assembled using a thermo-bond (heat-sealed) construction, includes a high tensile wire helix and light-duty fabric wearstrip around the circumference of the duct for abrasion resistance.
- GSL-W is an economy grade product that features a wide pitch construction to keep costs low.
- This product is recommended for positive airflow applications.

END FINISH

WIRE ROUND END RING

Wire ring encased in fabric interlocks one duct to another. This is our standard end finish.



SOFT CUFF WITH STRAP (CLIP)

Smaller diameters use a 1" (25mm) steel clip buckle.



SOFT CUFF

Folded fabric forms a 4" (102mm) finished cuff.



SOFT CUFF WITH STRAP (CAM)

Larger diameters use a 1" (25mm) cam buckle.

